

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Alabama		Height of headlamps must be at least 24" but no higher than 54".	Taillights & reflectors must be at a height of at least 20" but no more than 60".			Height including load not to exceed 13' 6".
Alaska	No height restrictions, but bumpers are required.	Height of headlamps must be at least 24" but no higher than 54".	Taillights minimum of 20'.		Lowest portion of body floor can be no more than 3" above top of frame. Maximum Frame height/ body floor height for a vehicle up to 4500 lbs. is 24", 4501-7500 lbs. is 26"; 7501-10000 lbs. is 28"	Height including load not to exceed 15'.
Arizona		Height of headlamps must be at least 22" but no higher than 54".	Taillights must be at a height of at least 15" but no more than 72".			Rear fender splashguards required for ¾-ton or lighter pickups if OEM bumper height has been increased. If vehicle height has been modified, then the mud flaps may be necessary.  Height including load not to exceed 13' 6".

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Arkansas		Height of headlamps must be at least 24" but no higher than 54".	Taillights must be at a height of at least 20" but no more than 72". Reflectors shall be mounted not less than 20" nor more than 60"			Height loaded or unloaded not to exceed 13' 6"
California		Height of headlamps must be at least 22" but no higher than 54".	Taillights for post 1969 vehicles must be at a height of at least 15" but no more than 72".		Maximum frame height for vehicles 4,500 lbs. or less t is 27"; 4,501 to 7,500 lbs. – 30"; and 7,501 to 10,000 – 31".	Note: lowest portion of the body floor can't be more than 5 inches above the top of the frame.  Overall height including load, not to exceed 14'.  Except that a double-deck bus may not exceed a height of 14' 3".
Colorado		Height of headlamps must be at least 24" but no higher than 54".	Taillights must be at a height of at least 20" but no more than 72". Every reflector shall be mounted on the vehicle at a height of not less than 20" nor more than 60".			No vehicle shall exceed a height of 13' except operated by the department of transportation with height of 14' 6"

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Connecticut	Height – OEM or 30"  Front bumper must be 3/16-inch thickness, pressed steel channel, not less than an 8" face, painted black, must protect outer edges of the fenders. Height: not more than 22".	Height of headlamps must be at least 22" but no higher than 54".	Taillights must be at a height of at least 15" but no more than 72".		No modifications that raise the sprung portion of the vehicle in excess of 4" above the vehicle's unladen height as established by the vehicle manufacturer	Maximum vehicle height loaded or unloaded not to exceed 13' 6"  No suspension springs which have a load carrying capacity or spring rate below that specified by the vehicle manufacturer.  With special permission granted, a vehicle can exceed 13'6" if loaded with loose hay or straw.
Delaware	Bumper height of passenger vehicle not to exceed 22" from ground to bottom of bumper. All other vehicles Maximum bumper height is 30" from bottom of bumper and ground.	Height of headlamps must be at least 24" but no higher than 54".	Taillights must be at a height of at least 20" but no more than 72".		Maximum distance between vehicle body and frame rail not to exceed 3" on passenger vehicles	Maximum vehicle height loaded or unloaded not to exceed 13' 6"
D. C.	Front bumpers are required in D.C.	Height of headlamps must be at least 24" but no higher than 54".	Taillights must be at a height of at least 15" but no more than 72".			Maximum vehicle height loaded or unloaded not to exceed 13' 6"

STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES

State	Bumpers	Headlights	Tail Lamps/ Reflectors	Tires	Frame body Modification	Other
Florida	<p><b>Autos for private use:</b> Less than 2,500 lbs. maximum height is 22" front and 22" rear. 2,500 to 3500 lbs. maximum height is 24" front and 26" rear; 3500 lbs. or more maximum height is 27" front and 29" rear.</p> <p><b>Trucks:</b> Less than 2,000 lbs., the maximum height is 24" front and 26" rear. More than 2,000 but less than 3,000, 27" front and 29" rear. Between 3,000 and 5,000, front 28" and rear 30".</p>	Height of headlamps must be at least 24" but no higher than 54".	2 tail lamps are required in Florida.			Maximum vehicle height loaded or unloaded not to exceed 13' 6"
Georgia		Height of headlamps must be at least 24" but no higher than 54".	Taillights must be at a height of at least 20" but no more than 60".		Less than 4500 lbs, maximum. 27" from surface of street to lowest point on frame; 4501 – 7500 lbs Maximum. 30" from surface of street to lowest point on frame. 7501 – 14000 lbs maximum. 31"	Maximum vehicle height loaded or unloaded not to exceed 13' 6"

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Hawaii	Maximum bumper height for passenger vehicles is 22". For vehicles 4,500 lbs. or less, front and rear bumper maximum height is 29"; 4,501 to 7,500 lbs., 33"; and 7,501 to 10,000 lbs. 35".	Height of headlamps must be at least 22" but no higher than 54".	2 tail lamps are required in Hawaii.		Allowable distance between the body and the frame rail 3".	Maximum vehicle height loaded or unloaded not to exceed 14'
Idaho	For vehicles 4,500 lbs. or less, front 24", rear 26"; 4,501 to 7,500 lbs., front 27"and back 29"; and 7,501 to 10,000 lbs., front 28" rear 30". However, 4x4s and dual-wheel trucks with a 10,000 pound or less front 30", rear 31".	Height of headlamps must be at least 24" but no higher than 54".	Taillights must be at a height of at least 20" but no more than 72".			Maximum vehicle height loaded or unloaded not to exceed 14'
Illinois	Maximum bumper height for vehicles 4,500 or less: front 24" and rear 26"; 4,501 to 7,500 front 27" and rear 29"; and 7,501 to 9,000, front 28" and rear 30". Over 9,000, front 28" and rear 30".				Body floor cannot be more than 4" above the frame. Maximum Frame height for vehicles with GVW less than 4500lbs. 24", 4500 to 7500lbs 26", 7501 to 10000lbs 28"	Height of vehicle from underside of tire to top of vehicle, inclusive of load, shall not exceed 13'6"

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Indiana	Passenger vehicle bumper height may not vary more than 3 inches from the original manufactured bumper height for the vehicle. Trucks of declared gross weight of not more than 11000 lbs. height of bumpers not to exceed 30 inches	Height of headlamps must be at least 24" but no higher than 54".	Tail lamp height of at least 20" but not more than 72" Reflectors must be mounted at a height of at least 20" but not more than 60"			Vehicle may not exceed a maximum height of 13' 6"
Iowa			Reflectors must be mounted at a height of at least 20" but not more than 42"			Vehicle may not exceed a maximum height of 13' 6"
Kansas		Height of headlamps must be at least 24" but no higher than 54".	Taillights must be at a height of at least 15" but no more than 72". Reflectors must be mounted at a height of at least 15" but not more than 60"			Height of vehicle including load shall not exceed 14'

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Kentucky		Height of headlamps must be at least 24" but no higher than 54".				Height of any vehicle not to exceed 11' 6".
Louisiana		Height of headlamps must be at least 24" but no higher than 54". (Fog lights maximum 30" from ground.)	Taillight height of at least 15" but not more than 72"		Vehicles must have at least 4" of ground clearance measured from frame with vehicle on a level surface.	Height of any vehicle not to exceed 13' 6"
Maine		Height of headlamps must be at least 22" but no higher than 54".		If the rim size has been altered, the overall diameter of the wheel with the tire must be within the vehicle manufacturer's specifications.	Frame height not to exceed 24" Front, 26" rear for vehicles less than 4501 lbs.; For vehicles 4501-7500 lbs. 28" front, 30" rear; and for vehicles 7501 – 10000 lbs. 30" front, 32" rear	Height of any vehicle not to exceed 13' 6"

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Maryland	Max. bumper height for passenger vehicles - 20". Max. bumper height for multipurpose vehicles - 28".	Height of headlamps must be at least 24" but no higher than 54"	Taillight height of at least 20" but not to exceed 72"		In a Class A (passenger) vehicle 20" maximum. In a Class M (multipurpose) vehicle 28" maximum.	Overall height including load cannot exceed 13' 6"
Massachusetts					Alterations not to exceed 2" more than OEM for vehicles up to 10000 lbs.	Formula for allowable height increase - maximum allowable increase to include larger tires Maximum Lift = (Wheelbase x Wheel Track) divided by 2200. (For example, formula may allow 2 inch lift and a 2 inch increase in tire, equaling a total lift of 4 inches over stock.)  Maximum height of any vehicle not to exceed 13' 6"

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Michigan	Passenger vehicle 22" bumper height. Less than 4,500 pounds 26" bumper height. 4,501-7,500 pounds 28" bumper height. 7,501-10,000 pounds 30" bumper height.	Height of headlamps must be at least 24" but no higher than 54". Vehicles licensed as a historic are exempt from this requirement if the vehicle as originally equipped failed to meet these requirements.			Passenger vehicle frame height on 12". Less than 4,500 pounds 24" frame height. 4,501-7,500 pounds 24" frame height. 7,501-10,000 pounds 26" frame height.	Lift blocks between the front axle and springs or lift blocks that exceed 4 inches in height between the rear axle and springs, are not allowed. Shackle replacements cannot exceed the OE length by more than 2 inches, and no coil-spring spacers.  Maximum height of any vehicle, loaded or unloaded, not to exceed 13' 6"
Minnesota	Must be within 6" of factory bumper height. Maximum bumper height for passenger vehicle is 20". Maximum bumper height for 4WD is 25".					Modifications to suspension system or bumper height of private passenger vehicles not to exceed more than 6" from OEM.  Maximum height of any vehicle, loaded or unloaded, not to exceed 13' 6"

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Mississippi			Reflectors can be mounted no higher than 60"			No vehicle can be modified in any way that will put it over the state's 8-inch total lift limit, and the maximum suspension lift front and rear is 6 inches to include tire.  Maximum height of any vehicle, loaded or unloaded, not to exceed 13' 6"
Missouri	Maximum bumper height: passenger vehicle 22" front 22" rear. GVWR 4500 lbs. or less front 24", rear 26"; 4501- 7500 lbs. 27" front, 29" rear; 7501-9000 lbs. 28" front, 30" rear		Taillights must be at least 15" but no more than 72".			Maximum height of any vehicle, loaded or unloaded, not to exceed 14'.
Montana		Height of headlamps must be at least 22" but no higher than 54".	Taillights must be at least 15" but no more than 72". Reflectors must be at least 15" but no more than 60".			Maximum height of any vehicle, loaded or unloaded, not to exceed 14'.

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Nebraska						Enforcement based on mud flaps, must block the entire width of the tires.  Total vehicle height, loaded or unloaded, not to exceed 14' 6"
Nevada		Height of headlamps must be at least 24" but no higher than 54".	Taillights must be at least 15" but no more than 72". Reflectors must be at least 15" but no more than 60".		Lowest portion of body can not exceed: 24" for passenger cars, 28" for vehicles up to 4500 lbs., 30" for 4501-7500 lbs.; 32" for 7501 – 10000 lbs.	Maximum vehicle height not to exceed 14'
New Hampshire	Max. bumper for passenger vehicle is 20". Trucks max. is 30". Minimum bumper height is 16".	Headlights must be at a height of at least 24" but no more than 54".	Taillights must be at a height of at least 20" but no more than 72".			Total vehicle height not to exceed 13' 6"
New Jersey	Bumpers are required if vehicle was originally equipped with bumpers.	Headlights must be at a height of at least 22" but no more than 54".	Taillights must be at a height no less than 15" but no more than 72".			Total vehicle height not to exceed 13' 6"  Maximum lift not to exceed: 7" above OVH for vehicles under 4500lbs., 9" above OVH for 4501-7500lbs, 11" above OVH for vehicles 7501-10000 lbs.

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
New Mexico		Headlights must be at a height of at least 20" but no more than 54".	Taillights must be at a height of at least 20" but no more than 72".			Total vehicle height, loaded or unloaded, not to exceed 14'
New York	For unloaded vehicle, no more than 30" of clearance between ground and front or rear bumper. The required height for bumpers is between 16 and 20" for all cars and SUVs.	Maximum height 54" above the ground	Maximum height 72".			Total vehicle height, loaded or unloaded, not to exceed 13' 6"
North Carolina		Maximum height of 42" above the ground.				Maximum total vehicle height, with or without load, not to exceed 13' 6"
North Dakota	All cars are required bumpers. Maximum bumper height is 27" Modified vehicles must have a bumper height between 14' and 22'.	Headlights must be at a height of at least 24" but no more than 54".	Taillights must be at a height of at least 15" but no more than 72".	Maximum outside diameter of tires is 44" for vehicles 7,000 pounds and under.		Maximum allowable lift for suspension system is 4". No modifications to OEM suspension, steering, or braking systems are allowed on vehicles weighing less than 7000 lbs. Maximum total vehicle height of 14'.

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Ohio	Vehicles 4,500 lbs. or less 24" front and 26" rear; 4,501 to 7,500 is 27" front and 29" rear; and 7,501 to 10,000, 28" front and 31" rear.				If the body or truck bed height is altered, the difference in height between the body floor and/or the bed floor to the top of the frame rail can be no more than 4 inches.	Total height, loaded or unloaded, not to exceed 13' 6"
Oklahoma		Headlights must be at a height of at least 22" but no more than 54".	Taillights must be at a height of at least 15" but no more than 72".			Total height, loaded or unloaded, not to exceed 13' 6"
Oregon		Maximum height 54" from the center of the headlight to the ground.				Total height of 14'.
Pennsylvania	Vehicles 5000 lbs. or less 24" front, 26" rear; 5001 – 7000 lbs. 27" front, 29" rear; 7001 – 9000 lbs. 28" rear, 30" front; 9001-11000 30" front and rear. Cars and SUVs 22' front and rear.	Headlights must be at a height of at least 24" but no more than 54".	Taillights must be at a height of at least 15" but no more than 72".			Total height, loaded or unloaded, not to exceed 13' 6"

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Rhode Island		Headlights must be at a height of at least 24" but no more than 54".	Taillights must be at a height of at least 20" but no more than 72".		Vehicles 10,000 lbs. or less, raise chassis or body, no more than 4 inches from the OEM height.	Total height, loaded or unloaded, not to exceed 13' 6"
South Carolina		Headlights must be at a height of at least 24" but no more than 54".	Taillights must be at a height of at least 20" but no more than 60".		It shall be unlawful for any person to drive a passenger motor vehicle which has been elevated or lowered either in front or back more than 6" by a modification, alteration or change in the physical structure of the vehicle.	General restriction based on height modification, no more than 6", higher or lower, from OEM height excludes 'pickup trucks'.  Total height, loaded or unloaded, not to exceed 13' 6"
South Dakota			Taillights must be at a height of at least 15" but no more than 72".			Total height not to exceed 14' 3"

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Tennessee					No more than 4 inches between the body floor and the top of the frame. Maximum frame heights: GVW 4,500 and less – 24"; 4,501 to 7,500 – 26"; and 7,501 to 10,000 – 28".	Modifications to front end using lift blocks is prohibited  Total height, loaded or unloaded, not to exceed 13' 6"
Texas		Headlamps must be mounted between 24" and 54" from the ground	Taillights must be at a height of at least 15" but no more than 72".			Total height, loaded or unloaded, not to exceed 13' 6"
Utah					Body floor not to be raised more than 3" above top of frame. Frame height not to exceed 24" for vehicles less than 4,500 lbs.; 26" for 4,501-7,500 Lbs. And 28" for 7,501 lbs and up.	Mud flaps required if frame height has been altered or vehicle is more than 10500 lbs.  Total height, loaded or unloaded, not to exceed 14'

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
Vermont	Vehicles 4,500 lbs. and less – 24” front and 26” rear; 4,501 to 7,500 – 27” front and 29” rear; and 7,501 to 10,000 - 28” front and 31” rear.					Total height not to exceed 13' 6"
Virginia	Vehicles 4500 or less no less than 14” nor more than 28” front and back. Vehicles 4,501 to 7,500 lbs. – no less than 14” nor more than 29” front and 30” rear; and 7,501 and 15,000 lbs. – no less than 14” front nor more than 31” rear.				No motor vehicle whose front-end suspension has been modified using lift blocks shall be driven on any highway in the Commonwealth.	Total height loaded or unloaded not to exceed 13' 6"
Washington	Max. bumper height passenger vehicles - 22". Max. bumper height for all other vehicles with a GVWR of: •4,500 lbs or less - 24" front and 26" rear; •4,501 to 7,500 lbs - 27" front and 29" rear; •7,501 lbs or more - 28" front and 30" rear.	Headlights must be at a height of at least 24” but no more than 54”.	Taillights must be at a height of at least 15” but no more than 72”.			Specific restrictions with overall height raising limits. Must be kit designed specifically for make and model of vehicle and correctly installed. Body lifts can not use more than a 3” spacer and are not allowed to raise the body more than 4 inches above the frame after all the components are installed.  Total height loaded or unloaded not to exceed 14’.

**STATE (US) LAWS IMPACTING ALTERED-HEIGHT VEHICLES**

<b>State</b>	<b>Bumpers</b>	<b>Headlights</b>	<b>Tail Lamps/ Reflectors</b>	<b>Tires</b>	<b>Frame body Modification</b>	<b>Other</b>
West Virginia	The front and rear bumper height for Vehicles with GVW 10,000 lbs or less may be no less than 6" and no more than 31"	Headlights must be at a height of at least 24" but no more than 54".	Taillights and reflectors must be at a height of at least 20" but no more than 60".		Maximum allowable space between the body and the frame is 3".	Total height loaded or unloaded not to exceed 13'6".
Wisconsin	Car bumpers must be within 2" of factory bumper height. Truck bumpers must be within 9" of factory bumper height.	Headlights must be at a height of at least 24" but no more than 54".	Taillights must be at a height of at least 20" but no more than 72".	Tires can be increased by up to 4 inches in radius over OEM for 4WD vehicles or trucks under 8000 lbs.	Cannot modify suspension, axles; or chassis more than 4" from OEM	Total height loaded or unloaded not to exceed 13'6".
Wyoming						Total height loaded or unloaded not to exceed 14'.